



Enter the “Microscopy University” on the web and discover a whole new world.

MicroscopyU  
[www.microscopyu.com](http://www.microscopyu.com)

Nikon’s International Small World Photomicrography Competition



<http://www.nikonsmallworld.com>

The products detailed in the brochure are controlled by the Japanese Foreign Exchange and Foreign Trade Law and the International Export Control Regime. If there is a possibility that they may be utilized for the development of weapons of mass destruction, etc., they shall not be exported without authorization from the government.

Monitor images are simulated.  
Company names and product names appearing in this brochure are their registered trademarks or trademarks.

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. May 2009 ©2005-9 NIKON CORPORATION

|  |                |
|--|----------------|
|  | <b>WARNING</b> |
| TO ENSURE CORRECT USAGE, READ THE CORRESPONDING MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT. |                |

|  |  |
|--|--|
|  |  |
| ISO 9001 Certified<br>NIKON CORPORATION<br>Instruments Company |  |
|  |  |
| ISO 14001 Certified<br>NIKON CORPORATION                       |  |





**NIKON CORPORATION**  
6-3, Nishiohi 1-chome, Shinagawa-ku, Tokyo 140-8601, Japan  
phone: +81-3-3773-8973 fax: +81-3-3773-8986  
<http://www.nikon.com/instruments/>

**NIKON INSTRUMENTS INC.**  
1300 Walt Whitman Road, Melville, N.Y. 11747-3064, U.S.A.  
phone: +1-631-547-8500; +1-800-52-NIKON (within the U.S.A. only)  
fax: +1-631-547-0306  
<http://www.nikoninstruments.com/>


**NIKON INSTRUMENTS EUROPE B.V.**  
Laan van Kronenburg 2, 1183 AS Amstelveen, The Netherlands  
phone: +31-20-44-96-222 fax: +31-20-44-96-298  
<http://www.nikoninstruments.eu/>

**NIKON INSTRUMENTS (SHANGHAI) CO., LTD.**  
CHINA phone: +86-21-5836-0050 fax: +86-21-5836-0030  
(Beijing branch) phone: +86-10-5869-2255 fax: +86-10-5869-2277  
(Guangzhou branch) phone: +86-20-3882-0552 fax: +86-20-3882-0580



# Biological Microscopes

# Superior optical products deliver the total solution



Listening carefully to customer voices while striving for increasingly higher quality, Nikon has developed a number of revolutionary technologies. Lenses with minimized aberration, for example, provide bright and clear images throughout the field of view. And technologies that integrate control of the microscope and peripherals systemize the sequence from experiment to imaging and analysis. With a wide array of optical products, Nikon supports constant evolution in the field of advanced bioscience.

## Contents

|   | Motorized Focusing | Macro Display | Brightfield       | Darkfield | DIC | Phase Contrast | Polarizing | Epi-Fluorescence | NAMC <sup>*1</sup> | Page |
|---|--------------------|---------------|-------------------|-----------|-----|----------------|------------|------------------|--------------------|------|
| Inverted Microscopes                      |                    |               |                   |           |     |                |            |                  |                    |      |
| Ti-E                                      | ✓                  |               | 100W (30W)        | ✓         | ✓   | ✓              |            | 100W             | ✓                  | 4    |
| Ti-U                                      |                    |               | 100W (30W)        | ✓         | ✓   | ✓              |            | 100W             | ✓                  | 4    |
| Ti-S                                      |                    |               | 100W (30W)        | ✓         | ✓   | ✓              |            | 100W             | ✓                  | 4    |
| TS100/TS100-F                             |                    |               | 30W               |           |     | ✓              |            | 50W              | ✓                  | 6    |
| Time-lapse Imaging System                 |                    |               |                   |           |     |                |            |                  |                    |      |
| BioStation IM                             | ✓                  | ✓             | LED               |           |     | ✓              |            | 130W             |                    | 7    |
| Upright Microscopes                       |                    |               |                   |           |     |                |            |                  |                    |      |
| 90i                                       | ✓                  |               | 100W              | ✓         | ✓   | ✓              | Simple     | 100W             |                    | 8    |
| 80i                                       |                    |               | 100W              | ✓         | ✓   | ✓              | Simple     | 100W             |                    | 8    |
| 55i                                       |                    |               | LED               |           |     |                |            | 100W             |                    | 9    |
| 50i                                       |                    |               | 30W               | ✓         |     | ✓              | Simple     | 100W             |                    | 9    |
| E200                                      |                    |               | 20W (30W)         | ✓         |     | ✓              | Simple     | 50W              |                    | 10   |
| E100                                      |                    |               | 20W               | ✓         |     | ✓              |            |                  |                    | 11   |
| Digital Microscope                        |                    |               |                   |           |     |                |            |                  |                    |      |
| COOLSCOPE II                              | ✓                  | ✓             | LED               |           |     |                |            |                  |                    | 11   |
| Polarizing Microscopes                    |                    |               |                   |           |     |                |            |                  |                    |      |
| LV100POL                                  |                    |               | 50W <sup>*2</sup> |           |     |                | ✓          |                  |                    | 12   |
| 50iPOL                                    |                    |               | 30W               |           |     |                | ✓          |                  |                    | 12   |
| E200POL                                   |                    |               | 20W (30W)         |           |     |                | ✓          |                  |                    | 12   |
| Microscope for Patch Clamp Experiments    |                    |               |                   |           |     |                |            |                  |                    |      |
| FN1                                       |                    |               | 100W              |           | ✓   |                |            | 100W             |                    | 12   |
| Multi-purpose Zoom Microscopes            |                    |               |                   |           |     |                |            |                  |                    |      |
| AZ100                                     |                    |               | 100W              |           | ✓   |                | Simple     | 130W             |                    | 13   |
| AZ100M                                    | ✓                  |               | 100W              |           | ✓   |                | Simple     | 130W             |                    | 13   |
| Stereoscopic Microscopes                  |                    |               |                   |           |     |                |            |                  |                    | 13   |
| Confocal Microscope Systems               |                    |               |                   |           |     |                |            |                  |                    | 15   |
| CCD Cameras                               |                    |               |                   |           |     |                |            |                  |                    | 16   |
| Software                                  |                    |               |                   |           |     |                |            |                  |                    | 17   |
| CFI60 Objectives                          |                    |               |                   |           |     |                |            |                  |                    | 18   |
| Combinations of DIC Prisms and Objectives |                    |               |                   |           |     |                |            |                  |                    | 20   |
| Epi-fluorescence Filters                  |                    |               |                   |           |     |                |            |                  |                    | 21   |
| Dimensional Diagrams                      |                    |               |                   |           |     |                |            |                  |                    | 22   |

\*1 Nikon Advanced Modulation Contrast

\*2 Brighter than 100W

Inverted Research Microscopes

## ECLIPSE Ti Series



### Ultimate solution for advanced imaging methods in live cell research

- Ti-E with motorized focusing and motorized four-port changeover, Ti-U with manual four-port changeover and Ti-S with manual two-port changeover
- High-speed multi-channel screening is possible by fast motorized control (Ti-E)
- Perfect Focus System (PFS) keeps in focus in real-time during long-term observation (Ti-E)
- Imaging software NIS-Elements provides total system control for 6D time-lapse imaging (Ti-E)
- “Full intensity” external phase contrast unit allows use of specialized objectives without a phase ring and acquisition of high-quality images with high NA objectives
- Nikon original stratum structure allows simultaneous mounting of multiple fluorescence turrets and simultaneous acquisition of multiple wavelengths with two cameras including optional back port
- By attaching a HUB controller, desired components such as TIRF and filter turret, in addition to the stage and nosepiece can be motorized



Ti-E configuration with motorized accessories



Ti-U configuration with epi-fluorescence illuminator



Ti-S

### Accessories for Ti Series

#### Motorized/Manual Laser TIRF Illuminator Unit (for Ti-E/U)

- Enables visualization of a single molecule with extraordinary high S/N ratio
- Imaging within approx. 100 nm from the coverslip-specimen interface with an evanescent wave
- The motorized TIRF system enables motorized control of laser incident angle from a PC or remote controller as well as storage and recall of up to four angles
- Laser TIRF, surface reflection interference contrast, and epi-fluorescence observations are switchable
- TIRF objective with correction ring adjusts image deteriorations caused by temperature changes



#### Epi-fl Illuminator Unit with White Light TIRF (for Ti-E/U/S)



- Handy and cost-effective TIRF observation using white light such as mercury illumination
- White light TIRF, oblique light fluorescence, surface reflection interference contrast, and epi-fluorescence observations are switchable
- The wide wavelength band of white light makes multiple wavelength TIRF observation possible by changing the filter

#### TIRF Photo Activation Illuminator Unit (for Ti-E/U)



- A laser TIRF illuminator, photo activation unit and epi-fluorescence illuminator have been combined in a single unit
- Switching between the three functions is easy

#### Photo Activation Illuminator Unit (for Ti-E/U)



- Photo activation and photo conversion using proteins such as PA-GFP and Kaede are possible
- Realizes photo activation of an arbitrary determined spot
- Photo activation and epi-fluorescence observation are switchable

## Inverted Microscopes

### ECLIPSE TS100/TS100-F

CFI60

New Apodized Phase Contrast objectives visualize minute details with greater resolution  
Also supports fluorescence and NAMC\*

- Adopts CFI60 infinity optics for this class of microscope
- Apodized Phase Contrast objectives visualize minute details within a specimen
- Both models support fluorescence microscopy
- Nikon Advanced Modulation Contrast (NAMC) observation is possible, enabling colorless and transparent samples in a plastic dish to be observed in high relief, a procedure not possible with DIC observation
- Eyepiece tube inclination and comfortable eye-point height for natural viewing posture when sitting or standing
- Low-profile 195mm-high stage with transparent acrylic stage ring for easy confirmation of objective in use
- Quintuple backward-facing nosepiece offers plenty of clearance for easy rotation



TS100 (Binocular tube model)

TS100-F (Trinocular tube model)

\*Nikon Advanced Modulation Contrast

## Accessories for Inverted Microscopes

### Stage Incubation System INU Series (for Ti-E/U/S, TS100/100F)

It sustains the internal temperature at 37°C with humidity of 90% and CO<sub>2</sub> of 5% to keep the specimen in a stable and precise condition for about three days.

(Manufactured by Tokai Hit Co., Ltd.)



### Thermal Plate Warmer

### ThermoPlate MATS Series (for Ti-E/U/S, TS100/100F)

A temperature controllable stage ring with a glass heating plate keeps the specimen at a set temperature. Temperature is adjustable from room temperature to 50°C in 0.1°C increments.

(Manufactured by Tokai Hit Co., Ltd.)



### HG Precentered Fiber Illuminator "Intensilight" (for Ti-E/U/S, i-series upright microscopes, AZ100/100M multi-purpose zoom microscopes)

Long-life mercury light source, suitable for fluorescence observation

- Precentered lamp — easy lamp replacement, no alignment required
- Average lamp lifetime as long as 2,000 hours
- Fiber connection — less heat and electrical noise conducted to microscope body. Ideal for time lapse and other lengthy observations
- Constant, non-fluctuating light intensity through a direct current (DC) lighting
- Motorized model available — shutter and light intensity controllable from PC or remote controller



## Accessories for Inverted Microscopes


### Oil Hydraulic Micromanipulation Systems

### NT-88-V3 Series (for Ti-E/U/S, TS100/100F)

The NT-88-V3 series provides microscopic and precise specimen micromanipulation for experiments in the fields of IVF (In Vitro Fertilization), especially ICSI (Intracytoplasmic Sperm Injection), transgenic biotechnology, and electrophysiology.

- Assembly of the micromanipulator is fast and easy due to the one-piece, extremely stable mounting adapter
- Easy-to-use hanging-type joystick
- Smooth operation without needle drift
- Needle top can be easily adjusted thanks to alignment indicators on the coarse unit
- Compact and stable design (less than half the size of conventional models)

(Manufactured by Narishige Co., Ltd.)



### Water Hydraulic Micromanipulation System

### MHW-3 (for Ti-E/U/S, TS100/100F)

Needle drift caused by changes in room temperature has been decreased to the lowest possible level. Optimized for long hours of micromanipulation, such as in electrophysiologic patch-clamp experiments.

(Manufactured by Narishige Co., Ltd.)



## Time Lapse Imaging System

### BioStation IM

The perfect solution for stable, long-term time-lapse imaging

- Incorporates a microscope, an incubator and a cooled CCD camera into a single system
- Consistent environmental control of temperature at 37°C, humidity at 95% or higher, and CO<sub>2</sub> concentration at 5%
- Total control of temperature of whole unit minimizes focus drift caused by temperature change
- Motorized objective lens movable in X, Y and Z directions eliminates focus drift caused by stage movement
- Exceptional phase contrast and fluorescence imaging quality
- Easy operation with fully motorized control from PC
- Optional ergo controller offers operational feel similar to that of an actual microscope
- Convenient accessories include the perfusion components that fit inside the incubator and a quadrant culture dish that does not cause the media's meniscus



Motorized Advanced Research Microscope

# ECLIPSE 90i



## Efficient automation in observation and imaging

- Motorized operation model with control capability from buttons on the microscope body, ergo controller, DS-L2 camera controller or a PC
- High-precision motorized focusing
- Motorized switching between observation methods, for example, from epi-fluorescence to DIC
- Aperture and brightness are automatically adjusted following the change of the magnification
- In a combination with the DS series camera, auto focus in brightfield is possible. Microscope status data can be automatically recorded with images
- Revolutionary Fly-Eye optics offers an excellent even illumination for digital imaging
- Improved DIC prisms offer optimal contrast and resolution



Configured with the digital imaging head DIH-E, C1 series confocal scanner and DS series CCD camera

Advanced Research Microscope

# ECLIPSE 80i



## Revolutionary optics perfect for digital imaging

- Manual operation model, but with the motorizing capability to, for example, switch magnifications or excitation filters by using the DIH-E digital imaging head, motorized DIC nosepiece or motorized epi-fluorescence illuminator
- In a combination with the DS series CCD camera, microscope status data can be automatically recorded with images
- Revolutionary Fly-Eye optics offer an excellent even illumination for digital imaging
- Improved DIC prisms offer optimal contrast and resolution



Configured with epi-fluorescence illuminator and DS series CCD camera

Clinical & Laboratory Microscopes

# ECLIPSE 55i/50i



## The ultimate in comfort that takes clinical microscopy to new heights

- 55i incorporates LED illumination-featuring a constant color temperature and lower power consumption-which is paramount for brightfield
- 50i adopts a halogen light source with a built-in ND8 filter for various observation methods
- Ergonomic Tube matches varying eyepoints. A digital camera is also attachable with an optional DSC port
- Hard finish stage with smooth XY movement, featuring height adjustable stage handle
- A retrofittable compact Cytodiagnostic Unit enables quick switching between 10x and 40x using a hand switch. When attached to 55i, it also keeps a constant brightness
- Refocusing stage facilitates specimen exchange
- Dedicated Epi-Fluorescence illuminator incorporates a 4-position filter turret with a lock mechanism to one or two positions



50i configured with epi-fluorescence attachment

55i configured with Ergonomic Tube

## Accessories for i Series Upright Microscopes


### Motorized Universal Epi-Fluorescence Attachment (for 80i)

Remote controller has CW/CCW switches for rotation of epi-fluorescence filter turret and epi-shutter IN/OUT switch



### Simple Polarizing Accessories (for 90i, 80i, 50i)

For observing birefringent samples such as collagen, amyloids and crystals



Simple Polarizing set A

Simple Polarizing set B (with swing-out rotatable polarizer)

Sextuple Nosepiece with Analyzer Slot (with swing-out rotatable polarizer)

### Drawing Tube (for 90i, 80i, 55i, 50i)

Microscope images can be easily traced while being observed

- Original optical system delivers images of 1x without a relay lens
- Low-magnification drawing kit available for drawing wider areas



### Double Port (for 90i, 80i, 55i, 50i)

Mounted between a microscope body and trinocular tube, the double port enables the simultaneous mounting of two cameras.



## Accessories for i Series Upright Microscopes

### Sensitive Color Polarizing Accessories (for 90i, 80i, 50i)

For gout and pseudo-gout tests



### Teaching Heads (for 90i, 80i, 50i)

The 50i can be configured with a two-person side-by-side or face-to-face version. The 90i/80i has versions that can handle up to 10 people. Structures can be selected flexibly, depending on use.



Thermal Plate Warmer

### ThermoPlate MATS Series (for 90i, 80i, 55i, 50i)

ThermoPlate MATS-U505S facilitates the thermal control of the specimen being observed. (rectangular type, W142 x D115 mm) (Manufactured by Tokai Hit Co., Ltd.)



### Quadrocular Adapter (for 90i, 80i, 55i, 50i)

Two cameras can be simultaneously mounted on a trinocular eyepiece tube via this adapter and switched.



### Magnification Module (for 90i, 80i, 55i, 50i)

The turret system allows the intermediate magnification to be changed from 1x to 1.25x, 1.5x or 2x.



### HG Precentered Fiber Illuminator “Intensilight” (for 90i, 80i, 55i, 50i, Ti-E/U/S inverted microscopes, AZ100/100M multi-purpose zoom microscopes)

See page 7 for details.

## Upright Microscope

Educational Microscope

### ECLIPSE E100

#### High optical quality, simple operation and rigid design

- CFI optical system and dedicated objectives for flat images
- Siedentopf-type eyepiece tube and eye level adjustments; digital camera attachable to trinocular eyepiece tube
- Phase contrast observation for high-contrast viewing of transparent and colorless specimens
- Durable, easy-to-rotate quadruple nosepiece
- Condenser comes with aperture diaphragm that has position-guide markings for 4/10/40/60/100x
- Anti-mold treatment for objectives, eyepieces, and eyepiece tube



E100 (Halogen lamp model)

## Digital Microscope

### COOLSCOPE II

CFI60



- Simultaneous Micro/Macro image display
- Memory function
- One-click stage shift
- Auto Focus
- Auto aperture/brightness adjustment
- Images saved on CompactFlash cards or USB memory stick, as well as other PCs via USB connection
- Direct connection to a printer means images can be printed without the use of a PC
- Magnification
  - Standard magnification type (5x, 10x, 20x, 40x)
  - Low magnification type (2x, 4x, 20x, 40x)
- SXGA high-definition image quality

#### All-in-one digital microscope that transcends the current concept of a microscope On-monitor observation, mouse-click operation

- Minimal configuration with just a tower main unit, monitor and mouse
- Simple mouse clicks do the rest once the preparation is loaded
- Elimination of microscope setups and optical adjustments
- No more stooping over eyepieces—just observe the specimen on the monitor in a relaxed posture
- Built-in digital camera for one-click image save as you see it on the monitor
- Optional ergonomic controller provides an operational feel similar to that of an actual microscope
- Just connect COOLSCOPE II to a projector for conference
- Network capabilities enable observation and control of COOLSCOPE II via Internet Explorer—convenient for consultation from a remote place

## Upright Microscope

Clinical & Educational Microscope

### ECLIPSE E200

#### Outstanding cost performance—striking image sharpness, operability and durability

- Adopts CFI60 infinity optics for this class of microscope. Plan objectives that excel in image flatness come standard
- One-touch refocusing stage for easier specimen handling
- Focusing knob and stage handle are low-positioned and equidistant from operator, permitting one-handed operation in natural posture
- Ergonomic binocular tube and eye-level risers are available for adjusting the eyepoint
- Anti-mold treated
- E200-F (model with field diaphragm) is also available
- Various accessories are available, such as dedicated epi-fluorescence attachment



CFI60

## Polarizing Microscopes

### ECLIPSE LV100POL/50iPOL/E200POL

CFI60

CFI60 infinity optics provide greater sharpness on polarizing regions

- CFI60 optics deliver world-class optical performance
- Excellent basic performance, operability, durability and, above all, outstanding image sharpness
- LV100POL is a research polarizing microscope that boasts twice the rigidity of conventional models and a brightness exceeding 100W (12V-50W model with centering quintuple nosepiece). The built-in Fly-Eye optics ensures uniform illumination, making it ideal for digital imaging
- ECLIPSE 50iPOL is compact yet possesses high functionality, such as a nosepiece with DIN standard compensator slot (6V-30W model with centering quintuple nosepiece)
- E200POL is a cost-efficient and extremely compact model (6V-20W model with quadruple nosepiece)



LV100POL



50iPOL



E200POL

## Multi-purpose Zoom Microscope

### Multizoom AZ100/AZ100M

Continuously switchable magnifications, extending from macro to micro observation of the same specimen

- Covers a magnification range of 5x to 400x, thanks to 8x zooming optics and a unique triple nosepiece
- True on-axis observation and image capture are possible in the macro region
- Comes standard with an aperture stop
- Tilting trinocular eyepiece tubes can accommodate a digital camera
- Focusing can be achieved with either the AZ stand or stage controls
- Because the stand section offers an 85mm stroke and the stage section a 10mm stroke, even tall samples can easily be observed
- AZ100M with motorized focusing and motorized zooming makes it easy to capture Extended Depth of Focus (EDF) images
- HG Precentered Fiber Illuminator "Intensilight" can be used (See page 7 for details)



AZ100M configured with Epi-FI attachment



AZ100 configured with Epi-FI attachment

## Microscope for Patch Clamp Experiments

### ECLIPSE FN1

CFI60

Dedicated patch-clamp microscope with I-shaped body design—more room for smooth electrode manipulation

- Multi Patch System motorizes viewfield changeover without having to move the specimen and objective
- Corrects axial chromatic aberration up to IR light (to 850nm). New 40x and 60x objectives for crisp high resolution IR-DIC imaging
- 100x objective with NA 1.1 and working distance 2.5mm comes with a correction function for depth- and thermally-induced aberrations
- Vertical motion nosepieces enables magnification changes without moving Petri dish (15mm or less in height)
- Easy switching between IR light and reflected illumination
- With an optional variable magnification double port (0.35x, 2x, 4x), both wide field and high magnification observations can be carried out with a 16x objective alone



All objectives have wide approach angles and long working distances (45° and 3.5mm with 40x objective).



Configuration with Narishige micromanipulators and epi-fluorescence attachment

## Stereoscopic Microscopes

### Parallel-optics System

- Nikon's unique OCC illumination (Oblique Coherent Contrast) is available with a C-DSD diascope stand, allowing colorless, transparent samples to be observed in high relief
- Various accessories, such as epi-fluorescence attachment, teaching head, simple polarizing set, are available
- Eyepiece tube is exchangeable from 20° inclination, low eyelevel, tilting eyepiece tube

### Stereoscopic Zoom Microscope SMZ1500

Top-of-the-line stereoscopic zoom microscope boasting a 15x zoom ratio, and high NA and resolution.



Configured with C-DSD diascope stand

### Stereoscopic Zoom Microscope SMZ1000

A 10x zoom ratio stereoscopic microscope offering superb optical performance and ergonomic operability.



Configured with C-PS160 plain stand

### Stereoscopic Zoom Microscope SMZ800

An affordable stereoscopic zoom microscope with a 6.3x zoom ratio offering excellent optical performance and expandability.



Configured with C-PS plain stand

## Stereoscopic Microscopes

### ■ Twin Objective System

Stereoscopic Zoom Microscopes

# SMZ645/660

# SMZ445/460

- SMZ645 and SMZ445 have 45° eyepiece inclination for comfortable viewing. SMZ660 and SMZ460 with 60° inclination are suitable for system integration
- Zoom ratio is 6.3x for SMZ645/660, 4.4x for SMZ445 and 4.3x for SMZ460
- The new hybrid type long-life LED stand features built-in diascope and angle-adjustable episcopic illumination. Both illuminations can be used simultaneously



New

Stereoscopic Microscope

# SM-5

Compact yet sturdy, its flexible design permits easy attachment to various instruments in production and quality control facilities at minimum costs.



### Accessories for Stereoscopic Microscopes

Thermal Plate Warmer

### ThermoPlate MATS Series (for diascope stands)

ThermoPlate MATS series facilitates the thermal control of the specimen being observed.  
(Manufactured by Tokai Hit Co., Ltd.)



MATS-USMZSL  
(fitted with base of C-DSS/DSD/BD stands)



MATS-USMZSS  
(fitted with base of C-DS diascope stand)



MATS-USMZR  
(ring type ø180mm)



MATS-U4020WF  
(wide working-area type W430 x D205 x H75-100mm; glass thickness 1.6mm)

## Confocal Microscope Systems

Confocal Microscope

# A1R/A1

The A1R with a revolutionary hybrid scanner realizes ultrafast and high-resolution imaging

- Hybrid scanner capable of high-speed imaging at 420 fps (512 x 32 pixels) allows simultaneous imaging and photo activation (A1R)
- High-resolution imaging up to 4096 x 4096 pixels
- With the VAAS pinhole unit, flare can be eliminated and image brightness retained. Moreover, different sectioning can be simulated after image acquisition
- Dichroic mirror with 30% increased fluorescence efficiency provides high image quality



Configured with Ti-E

New

True Spectral Imaging Confocal Microscope

# A1Rsi/A1si

High-performance spectral detector supports simultaneous excitation of multiple wavelengths

- Acquisition of 32 channels (512 x 32 pixels) at 24 fps in a single scan
- Accurate, real-time spectral unmixing
- Simultaneous excitation of four lasers
- V-filtering function adjusts total intensity of up to four desired spectral ranges individually, providing flexibility to handle new fluorescence probes



Configured with Ti-E

New

Confocal Microscope

# C1 plus

Personal confocal microscope now supports FRAP

- 1000x optical zoom of ROI
- ROI scanning is possible with an optional AOM/AOTF
- Accommodates a greater variety of lasers with wavelengths ranging from 405 to 640nm
- 4-channel simultaneous acquisition such as 3-channel confocal plus DIC



Configured with Ti-E

True Spectral Imaging Confocal Microscope

# C1si

Spectra across a wide 320nm range captured with a single scan

- High-speed, low-invasive imaging by a single scan acquisition
- Unmixing of spectral images without crosstalk
- Nikon's proprietary DEES and DISP technology for bright images
- Accuracy of spectra is maintained with diverse correction technologies




Configured with 90i

## Digital Camera System for Microscopes Digital Sight Series

The Digital Sight series offers a choice of seven camera heads and two control units, enabling an image capturing system to be assembled to suit each use.


**New** **Ultrahigh-resolution Cooled Color Camera Head DS-Ri1**

- 12.7-megapixel, 2200TV line high-definition images
- Faithful reproduction of specimen color
- Smooth display of live images
- Reduces heat noise; captures fluorescence and darkfield images clearly




**High-speed Cooled Monochrome Camera Head DS-2MBWc**

- Cooling mechanism enables it to capture fluorescence and darkfield images clearly
- High-frame-rate and high-sensitivity 2.0-megapixel CCD




**New** **High-definition Cooled Color Camera Head DS-Fi1c**

- Cooling mechanism enables it to capture fluorescence and darkfield images clearly
- High-definition 5.0-megapixel CCD




**High-definition Color Camera Head DS-Fi1**

- High-definition 5.0-megapixel CCD
- High resolution and high frame rate
- High dynamic range and accurate color reproduction




**High-sensitivity Cooled Monochrome Camera Head DS-Qi1**

- High sensitivity equivalent to ISO 800
- Cooling mechanism reduces dark current to 0.7e-/pixel/s and readout noise to 8e- rms, realizing a wide dynamic range
- Superior quantity with linearity of >98%



**High-speed Color Camera Head DS-2Mv**

- High-frame-rate, 2.0-megapixel CCD
- Suitable for monitoring of microscopy images



### PC-use Control Unit DS-U2



- Versatile image capture, processing, measurement and analysis when coupled with imaging software NIS-Elements
- High-speed image transfer to PC via USB 2.0 connection
- Compact, space-saving design
- Allows control of Nikon motorized microscopes


### Standalone Control Unit DS-L2



- Built-in high-definition 8.4-in. large LCD monitor
- Camera can be operated via the GUI of the LCD monitor, eliminating the necessity of PC connection
- Various digital interfaces including USB 2.0 connection
- Pre-programmed imaging modes for different observation methods
- Allows control of the Nikon motorized microscopes 90i/80i

## Imaging Software NIS-Elements

NIS-Elements is an integrated platform of imaging software developed by Nikon to achieve comprehensive control of microscope image capture and document data management. NIS-Elements handles multidimensional imaging tasks flawlessly with support for capture, display, peripheral device control, and data management & analysis of images (up to six-dimensional images).



Available in three distinct packages scaled to meet user needs and applications:

### Ar NIS-Elements Advanced Research

NIS-Elements AR is optimized for advanced research applications. It features fully automated acquisition and device control through full 6D (X, Y, Z, Lambda (Wavelength), Time, Multipoint) image acquisition and analysis.

### Br NIS-Elements Basic Research

NIS-Elements BR is suited for standard research applications. It features acquisition and device control through 4D (up to four dimensions can be selected from X, Y, Z, Lambda (Wavelength), Time, Multipoint) acquisition.

### D NIS-Elements Documentation

NIS-Elements D supports color documentation requirements in bio-research, clinical and industrial applications, with basic measuring and reporting capabilities.

Various convenient plug-ins are available for advanced imaging and analysis capabilities.

### Multidimensional Capturing

NIS-Elements can combine X, Y, Z, Lambda (wavelength), Time and Multi points within one integrated platform for multidimensional imaging (depending on the capability of the software). All combinations of multidimensional images can be linked together in one ND2 file sequence using an efficient workflow and intuitive GUI.



X, Y, Z,  $\lambda$  (Wavelength), T, Multipoint acquisition

### 3D/2D Real-time Deconvolution

Haze and blur of the fluorescence image can be eliminated from the captured 3D image or from the 2D live preview image. (Separate plug-in for 3D and 2DRT)

#### 3D Deconvolution



#### 2D Real-time Deconvolution



After deconvolution

### Extended Depth of Focus

With the Extended Depth of Focus (EDF) plug-in, images that have been captured in a different Z-axis can be used to create an all-in-focus image. Also, it is possible to create stereovision images & 3D surface images to achieve virtual 3D imaging.



All-in-focus image created from a sequence of Z-stack images

### Database

NIS-Elements has a powerful image database module that supports image and meta data. Various databases & tables can easily be created and images can be saved to the database via one simple mouse-click. Filtering, sorting and multiple grouping are also available according to the database field given for each image.



Visit [www.nis-elements.com](http://www.nis-elements.com) for more detailed information

CFI60 Objectives

| Type           | Use   | Model                    | Immersion | NA       | W.D. (mm) | Cover glass thickness | Correction ring | Spring loaded | Brightfield | Darkfield | DIC*5 | Phase contrast | Polarizing | Fluorescence |        | Ti-E PFS |
|----------------|---|--------------------------|-----------|----------|-----------|-----------------------|-----------------|---------------|-------------|-----------|-------|----------------|------------|--------------|--------|----------|
| Achromat       | Brightfield (CFI)                               | 4x                       |           | 0.10     | 30.00     | —                     |                 |               | ⊙           |           |       |                | △          | ○            |        |          |
|                |   | 10x                      |           | 0.25     | 7.00      | —                     |                 |               | ⊙           | △         |       |                | △          | ○            |        |          |
|                |   | LWD 20x                  |           | 0.40     | 3.90      | 0.17                  |                 |               | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | 40x                      |           | 0.65     | 0.65      | 0.17                  |                 | ✓             | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | LWD 40xC                 |           | 0.55     | 2.7-1.7   | 0-2.0                 | ✓               |               | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | 60x                      |           | 0.80     | 0.30      | 0.17                  |                 | ✓             | ⊙           | ●         |       |                | △          | ○            |        |          |
|                |   | 100xH                    | Oil       | 1.25     | 0.23      | 0.17                  |                 | ✓             | ⊙           |           |       |                | △          | ○            |        |          |
|                |   | 100xSH (with iris)       | Oil       | 0.5-1.25 | 0.23      | 0.17                  |                 | ✓             | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                | Polarizing (CFI)                                | P 4x                     |           | 0.10     | 30.00     | —                     |                 |               | ⊙           |           |       |                | ⊙          | ○            |        |          |
|                |   | P 10x                    |           | 0.25     | 7.00      | —                     |                 |               | ⊙           | △         |       |                | ⊙          | ○            |        |          |
|                |   | LWD P 20x                |           | 0.40     | 3.90      | 0.17                  |                 |               | ⊙           | ○●        |       |                | ⊙          | ○            |        |          |
|                |   | P 40x                    |           | 0.65     | 0.65      | 0.17                  |                 | ✓             | ⊙           | ○●        |       |                | ⊙          | ○            |        |          |
|                |   | P 100xH                  | Oil       | 1.25     | 0.23      | 0.17                  |                 | ✓             | ⊙           |           |       |                | ⊙          | ○            |        |          |
|                | Phase contrast (CFI)                            | DL 10x                   |           | 0.25     | 7.00      | —                     |                 |               | ○           | △         |       | ⊙ PH1          | △          | △            |        |          |
|                |   | LWD DL 20x               |           | 0.40     | 3.90      | 0.17                  |                 |               | ○           | ○●        |       | ⊙ PH1          | △          | △            |        |          |
|                |   | LWD DL 20xF              |           | 0.40     | 3.10      | 1.2                   |                 |               | ○           |           |       | ⊙ PH1          | △          | △            |        |          |
|                |   | DL 40x                   |           | 0.65     | 0.65      | 0.17                  |                 | ✓             | ○           | ○●        |       | ⊙ PH2          | △          | △            |        |          |
|                |   | LWD DL 40x               |           | 0.55     | 2.7-1.7   | 0-2.0                 | ✓               |               | ○           | ○●        |       | ⊙ PH2          | △          | △            |        |          |
|                |   | DL 100xH                 | Oil       | 1.25     | 0.23      | 0.17                  |                 | ✓             | ○           |           |       | ⊙ PH3          | △          | △            |        |          |
|                |   | BM 10x*1                 |           | 0.25     | 7.00      | —                     |                 |               | ○           |           |       | ⊙ PH1          | △          | △            |        |          |
|                |   | ADL 10x                  |           | 0.25     | 6.20      | 1.2                   |                 |               | ○           |           |       | ⊙ PH1          | △          | △            |        |          |
|                | Apodized phase contrast (CFI)                   | LWD ADL 20xF             |           | 0.40     | 3.10      | 1.2                   |                 |               | ○           |           |       | ⊙ PH1          | △          | △            |        |          |
|                |   | LWD ADL 40x F            |           | 0.55     | 2.10      | 1.2                   |                 |               | ○           |           |       | ⊙ PH1          | △          | △            |        |          |
|                |   | LWD ADL 40xC             |           | 0.55     | 2.7-1.7   | 0-2.0                 | ✓               |               | ○           | ○●        |       | ⊙ PH2          | △          | △            |        |          |
|                |   | LWD NAMC 40xC            |           | 0.55     | 2.7-1.7   | 0-2.0                 | ✓               |               | ○           |           |       |                |            | △            |        |          |
| Plan Achromat  | Brightfield (CFI Plan)                          | UW 1x                    |           | 0.04     | 3.20      | —                     |                 |               | ⊙           |           |       |                | △          | △            |        |          |
|                |   | UW 2x                    |           | 0.06     | 7.50      | —                     |                 |               | ⊙           |           |       |                | △          | △            |        |          |
|                |   | 4x                       |           | 0.10     | 30.00     | —                     |                 |               | ⊙           |           |       |                | △          | ○            |        |          |
|                |   | 10x                      |           | 0.25     | 10.50     | —                     |                 |               | ⊙           | △         |       |                | △          | ○            |        |          |
|                |   | 20x                      |           | 0.40     | 1.20      | 0.17                  |                 |               | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | 40x                      |           | 0.65     | 0.56      | 0.17                  |                 | ✓             | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | 50xH                     | Oil       | 0.90     | NCG0.35   | —                     |                 | ✓             | ⊙           | ●         |       |                | △          | ○            |        |          |
|                |   | 100xH                    | Oil       | 1.25     | 0.20      | 0.17                  |                 | ✓             | ⊙           |           |       |                | △          | ○            |        |          |
|                | Phase contrast (CFI Plan)                       | DL 10x                   |           | 0.25     | 10.50     | —                     |                 |               | ○           | △         |       | ⊙ PH1          | △          | △            |        |          |
|                |   | DL 20x                   |           | 0.40     | 1.20      | 0.17                  |                 |               | ○           | ○●        |       | ⊙ PH1          | △          | △            |        |          |
|                |   | DL 40x                   |           | 0.65     | 0.56      | 0.17                  |                 | ✓             | ○           | ○●        |       | ⊙ PH2          | △          | △            |        |          |
|                |   | DL 100xH                 | Oil       | 1.25     | 0.20      | 0.17                  |                 | ✓             | ○           |           |       | ⊙ PH3          | △          | △            |        |          |
|                | No cover glass (CFI Plan)                       | NCG 40x                  |           | 0.65     | 0.48      | 0                     |                 | ✓             | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | NCG 60x (CF objective)*2 |           | 0.85     | 0.35      | 0                     |                 | ✓             | ⊙           | ●         |       |                | △          | ○            |        |          |
|                |   | NCG 100x                 |           | 0.90     | 0.26      | 0                     |                 | ✓             | ⊙           | ●         |       |                | △          | ○            |        |          |
|                | Super long WD (CFI L Plan EPI)                  | SLWD 20x                 |           | 0.35     | 24.00     | 0                     |                 |               | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | SLWD 50x                 |           | 0.45     | 17.00     | 0                     |                 |               | ⊙           | ○●        |       |                | △          | ○            |        |          |
|                |   | SLWD 100x                |           | 0.70     | 6.50      | 0                     |                 |               | ⊙           | ○●        |       |                | △          | ○            |        |          |
| S Plan Fluor*3 | Brightfield (CFI S Plan Fluor)                  | ELWD 20xC                |           | 0.45     | 8.2-6.9   | 0-2.0                 | ✓               |               | ⊙           | ○●        | ○     |                | ○          | ⊙            | ○      | ●        |
|                |   | ELWD 40xC                |           | 0.60     | 3.6-2.8   | 0-2.0                 | ✓               |               | ⊙           | ○●        | ○     |                | ○          | ⊙            | ○      | ●        |
|                |   | ELWD 60xC                |           | 0.70     | 2.6-1.8   | 0.1-1.3               | ✓               |               | ⊙           | ○●        | ○     |                | ○          | ⊙            | ○      | ●        |
|                | Apodized phase contrast (CFI S Plan Fluor)      | ELWD ADM 20xC            |           | 0.45     | 8.2-6.9   | 0-2.0                 | ✓               |               | ○           | ○●        |       | ⊙ PH1          |            | ○            | ○      | ●        |
|                |   | ELWD ADM 40xC            |           | 0.60     | 3.6-2.8   | 0-2.0                 | ✓               |               | ○           | ○●        |       | ⊙ PH2          |            | ○            | ○      | ●        |
|                |   | ELWD ADL 60xC            |           | 0.70     | 2.6-1.8   | 0.1-1.3               | ✓               |               | ○           | ○●        |       | ⊙ PH2          |            | ○            | ○      |          |
|                | Advanced modulation contrast (CFI S Plan Fluor) | ELWD NAMC 20xC           |           | 0.45     | 7.40      | 0-2.0                 | ✓               |               | ○           |           |       |                |            | ○            |        |          |
|                |   | ELWD NAMC 40xC           |           | 0.60     | 3.10      | 0-2.0                 | ✓               |               | ○           |           |       |                |            | ○            |        |          |
| S Fluor*4      | Brightfield (CFI S Fluor)                       | 4x                       |           | 0.20     | 15.50     | —                     |                 |               | ⊙           |           |       |                | △          | ⊙            | ⊙ Wide | ●        |
|                |   | 10x                      |           | 0.50     | 1.20      | 0.17                  |                 | ✓             | ⊙           | ○●        | ○     |                | △          | ⊙            | ⊙ Wide | ●        |
|                |   | 20x                      |           | 0.75     | 1.00      | 0.17                  |                 | ✓             | ⊙           | ○●        | ○     |                | △          | ⊙            | ⊙ Wide | ●        |
|                |   | 40x                      |           | 0.90     | 0.30      | 0.11-0.23             | ✓               | ✓             | ⊙           | ●         | ○     |                | △          | ⊙            | ⊙ Wide |          |
|                |   | 40xH                     | Oil       | 1.30     | 0.22      | 0.17                  |                 | ✓w/stopper    | ⊙           |           | ○     |                | △          | ⊙            | ⊙ Wide | ●        |
|                |   | 100xSH (with iris)       | Oil       | 0.5-1.3  | 0.20      | 0.17                  |                 | ✓             | ⊙           | ○●        |       |                | △          | ⊙            | ⊙ Wide |          |
|                | Phase contrast (CFI S Fluor)                    | DL 20x*1                 |           | 0.75     | 1.00      | 0.17                  |                 | ✓             | ⊙           | ○●        |       | ⊙ PH2          |            | ○            | ○      | ●        |
|                |   | DL 40x*1                 |           | 0.90     | 0.30      | 0.11-0.23             | ✓               | ✓             | ⊙           | ●         |       | ⊙ PH2          |            | ○            | ○      | ●        |

\*1 Make-to-order

\*2 To use with the CFI60 optics microscope (not possible in E400), an objective conversion adapter is necessary.

\*3 Axial chromatic aberration is corrected in shorter wavelength ranges than the Plan Fluor series to improve image clarity.

\*4 Transmits an ultraviolet light up to a 340nm wavelength

\*5 See page 20 for compatible prisms

\*6 Dedicated for FN1 (CFI75 objective)

Note 1. Model numbers  
The below letters, when attached to the end of model numbers, indicate the respective features.  
  
H: oil immersion type  
F: for use with 1.2mm-thick cover glass  
C: with correction ring  
NCG: for use without cover glass

SH: with iris  
WI: water immersion type  
W: water dipping type  
Mi: multi immersion (oil, water, glycerin) type

Note 2. Cover glass thickness  
— : can be used without cover glass  
0: use without cover glass

Note 3. Darkfield microscopy  
Possible with the following  
△ : universal condenser (dry) and darkfield ring  
○ : above and darkfield condenser (dry)  
● : darkfield condenser (oil)

Note 4. Phase rings are classified by objective NA  
PHL: for Plan Fluor 4x  
PH1: NA 0.25 - 0.5  
PH2: NA 0.55 - 0.95  
PH3: NA 1.0 - 1.40  
PH4: NA 1.45 - 1.49  
EXT: compatible with external phase contrast of the Ti series

Note 5. Fluorescence microscopy (UV)  
△ : possible with visible light that has a longer wavelength than the excitation light used for DAPI  
○ : suitable  
⊙ : recommended for best results  
Wide: high transmittance with an ultraviolet wavelength range of up to 340nm

| Type                 | Use   | Model                | Immersion            | NA        | W.D. (mm)                           | Cover glass thickness | Correction ring                      | Spring loaded | Brightfield | Darkfield | DIC*5 | Phase contrast | Polarizing   | Fluorescence  |    | Ti-E PFS |   |
|----------------------|---|----------------------|----------------------|-----------|-------------------------------------|-----------------------|--------------------------------------|---------------|-------------|-----------|-------|----------------|--------------|---------------|----|----------|---|
|                      |   |                      |                      |           |                                     |                       |                                      |               |             |           |       |                |              | Visible light | UV |          |   |
| Universal Plan Fluor | No cover glass polarizing (CFI LU Plan Fluor EPI) | P 5x                 |                      | 0.15      | 23.50                               | —                     |                                      |               | ⊙           |           |       |                | ⊙            | ⊙             | ⊙  |          |   |
|                      |   | P 10x                |                      | 0.30      | 17.50                               | 0                     |                                      |               | ⊙           | △         |       |                | ⊙            | ⊙             | ⊙  |          |   |
|                      |   | P 20x                |                      | 0.45      | 4.50                                | 0                     |                                      |               | ⊙           | ⊙●        |       |                | ⊙            | ⊙             | ⊙  |          |   |
|                      |   | P 50x                |                      | 0.80      | 1.00                                | 0                     |                                      | ✓             | ⊙           | ●         |       |                | ⊙            | ⊙             | ⊙  |          |   |
|                      |   | P 100x               |                      | 0.90      | 1.00                                | 0                     |                                      | ✓             | ⊙           | ●         |       |                | ⊙            | ⊙             | ⊙  |          |   |
| Plan Fluor           | Brightfield (CFI Plan Fluor)                      | 4x                   |                      | 0.13      | 17.10                               | —                     |                                      |               | ⊙           |           |       |                | △            | ⊙             | ⊙  |          |   |
|                      |   | 10x                  |                      | 0.30      | 16.00                               | 0.17                  |                                      |               | ⊙           | △         | ○     |                | ○            | ⊙             | ⊙  | ●        |   |
|                      |   | 20x                  |                      | 0.50      | 2.10                                | 0.17                  |                                      |               | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  |          |   |
|                      |   | ELWD 20xC            |                      | 0.45      | 8.1-7.0                             | 0-2.0                 | ✓                                    |               | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  | ●        |   |
|                      |   | 20xMi                | Oil, water, glycerin | 0.75      | 0.51-0.35<br>0.51-0.34<br>0.49-0.33 | 0-0.17                | ✓                                    | ✓             | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  |          |   |
|                      |   | 40x                  |                      | 0.75      | 0.66                                | 0.17                  |                                      | ✓             | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  | ●        |   |
|                      |   | ELWD 40xC            |                      | 0.60      | 3.7-2.7                             | 0-2.0                 | ✓                                    |               | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  | ●        |   |
|                      |   | 40xH                 | Oil                  | 1.30      | 0.20                                | 0.17                  |                                      | ✓w/stopper    | ⊙           |           | ○     |                | ○            | ⊙             | ⊙  | ●        |   |
|                      |   | 60x                  |                      | 0.85      | 0.40-0.31                           | 0.11-0.23             | ✓                                    | ✓             | ⊙           | ●         | ○     |                | ○            | ⊙             | ⊙  |          |   |
|                      |   | ELWD 60xC            |                      | 0.70      | 2.1-1.5                             | 0.5-1.5               | ✓                                    |               | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  |          |   |
|                      |   | 60xSH (with iris)    | Oil                  | 0.50-1.25 | 0.22                                | 0.17                  |                                      | ✓             | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  |          |   |
|                      |   | 100x                 |                      | 0.90      | 0.32-0.28                           | 0.14-0.20             | ✓                                    | ✓             | ⊙           | ●         | ○     |                | ○            | ⊙             | ⊙  |          |   |
|                      |   | 100xH                | Oil                  | 1.30      | 0.16                                | 0.17                  |                                      | ✓w/stopper    | ⊙           |           | ○     |                | ○            | ⊙             | ⊙  | ●        |   |
|                      |   | 100xSH (with iris)   | Oil                  | 0.50-1.30 | 0.16                                | 0.17                  |                                      | ✓             | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | ⊙  |          |   |
|                      | Phase contrast (CFI Plan Fluor)                   | DL 4x                |                      | 0.13      | 16.40                               | 1.2                   |                                      |               | ○           |           |       | ⊙ PHL          |              | ○             | ○  |          |   |
|                      |   | DLL 10x              |                      | 0.30      | 16.00                               | 0.17                  |                                      |               | ○           | △         |       | ⊙ PH1          |              | ○             | ○  | ●        |   |
|                      |   | DL 10x               |                      | 0.30      | 15.20                               | 1.2                   |                                      |               | ○           | △         |       | ⊙ PH1          |              | ○             | ○  |          |   |
|                      |   | DLL 20x              |                      | 0.50      | 2.10                                | 0.17                  |                                      |               | ○           | ⊙●        |       | ⊙ PH1          |              | ○             | ○  |          |   |
|                      |   | DLL 40x              |                      | 0.75      | 0.66                                | 0.17                  |                                      | ✓             | ○           | ⊙●        |       | ⊙ PH2          |              | ○             | ○  | ●        |   |
|                      |   | DM 40xDS             |                      | 0.75      | 0.66                                | 0.17                  |                                      | ✓             | ○           | ⊙●        |       | ⊙ PH2          |              | ○             | ○  |          |   |
|                      |   | DLL 100xH            | Oil                  | 1.30      | 0.16                                | 0.17                  |                                      | ✓w/stopper    | ○           |           |       | ⊙ PH3          |              | ○             | ○  | ●        |   |
|                      | Apodized phase contrast (CFI Plan Fluor)          | ADH 100xH            | Oil                  | 1.30      | 0.16                                | 0.17                  |                                      | ✓w/stopper    | ○           |           |       | ⊙ PH3          |              | ○             | ○  | ●        |   |
| Plan Apochromat      | Brightfield (CFI Plan Apo)                        | 2x                   |                      | 0.10      | 8.50                                | —                     |                                      |               | ⊙           |           |       |                | ○            | ⊙             | △  |          |   |
|                      |   | 4x                   |                      | 0.20      | 20.00                               | —                     |                                      |               | ⊙           |           |       |                | ○            | ⊙             | △  | ●        |   |
|                      |   | 10x                  |                      | 0.45      | 4.00                                | 0.17                  |                                      |               | ⊙           |           | ○     |                | ○            | ⊙             | △  | ●        |   |
|                      |   | 20x                  |                      | 0.75      | 1.00                                | 0.17                  |                                      | ✓             | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | △  | ●        |   |
|                      |   | VC 20x               |                      | 0.75      | 1.00                                | 0.17                  |                                      | ✓             | ⊙           | ⊙●        | ○     |                | ○            | ⊙             | △  | ●        |   |
|                      |   | 40x                  |                      | 0.95      | 0.16-0.12                           | 0.11-0.23             | ✓                                    | ✓             | ⊙           | ●         | ○     |                | ○            | ⊙             | △  | ●        |   |
|                      |   | 40xH                 | Oil                  | 1.00      | 0.16                                | 0.17                  |                                      | ✓w/stopper    | ⊙           |           | ○     |                | ○            | ⊙             | △  |          |   |
|                      |   | 60x                  |                      | 0.95      | 0.17-0.13                           | 0.11-0.23             | ✓                                    | ✓             | ⊙           | ●         | ○     |                | ○            | ⊙             | △  |          |   |
|                      |   | VC 60xH              | Oil                  | 1.40      | 0.13                                | 0.17                  |                                      | ✓             | ⊙           |           | ○     | EXT PH3-60x    | ○            | ⊙             | △  | ●        |   |
|                      |   | VC60xA WI            | Water                | 1.20      | 0.31-0.28                           | 0.15-0.18             | ✓                                    | ✓             | ⊙           | ●         | ○     | EXT PH3-60x    | ○            | ⊙             | ⊙  | ●        |   |
|                      |   | VC 100xH             | Oil                  | 1.40      | 0.13                                | 0.17                  |                                      | ✓             | ⊙           |           | ○     | EXT PH3-100x   | ○            | ⊙             | △  | ●        |   |
|                      |   | NCG 100xH            | Oil                  | 1.40      | 0.16                                | 0                     |                                      | ✓             | ⊙           |           | ○     |                | ○            | ⊙             | △  |          |   |
|                      | Phase contrast (CFI Plan Apo)                     | DM 20x               |                      | 0.75      | 1.00                                | 0.17                  |                                      | ✓             | ○           | ⊙●        |       | ⊙ PH2          |              | ○             | △  |          |   |
|                      |   | DM 40x               |                      | 0.95      | 0.16-0.12                           | 0.11-0.23             | ✓                                    | ✓             | ○           | ●         |       | ⊙ PH2          |              | ○             | △  | ●        |   |
|                      |   | DM 40xH              | Oil                  | 1.00      | 0.16                                | 0.17                  |                                      | ✓w/stopper    | ○           | ●         |       | ⊙ PH3          |              | ○             | △  |          |   |
|                      |   | DM 60x               |                      | 0.95      | 0.17-0.13                           | 0.11-0.23             | ✓                                    | ✓             | ○           | ●         |       | ⊙ PH2          |              | ○             | △  |          |   |
|                      |   | DM 60xH              | Oil                  | 1.40      | 0.13                                | 0.17                  |                                      | ✓             | ○           |           |       | ⊙ PH3          |              | ○             | △  | ●        |   |
|                      |   | DM 100xH             | Oil                  | 1.40      | 0.13                                | 0.17                  |                                      | ✓             | ○           |           |       | ⊙ PH3          |              | ○             | △  | ●        |   |
|                      |   | Evanescent (CFI Apo) | TIRF 60xH            | Oil       | 1.49                                | 0.12                  | 0.13-0.19 (23°C)<br>0.15-0.21 (37°C) | ✓             |             | ⊙         |       | ○              | EXT PH4-60x  | ○             | ⊙  | △        | ● |
|                      |   |                      | TIRF 100xH           | Oil       | 1.49                                | 0.12                  | 0.13-0.19 (23°C)<br>0.14-0.20 (37°C) | ✓             |             | ⊙         |       | ○              | EXT PH4-100x | ○             | ⊙  | △        | ● |

Combinations of DIC Prisms and Objectives

For Ti series inverted microscopes

|   |   | System Condenser LWD Dry, Motorized System Condenser LWD Dry |                 |                  |            |                  |            | HNA Condenser Lens Dry |            |                  |            | HNA Condenser Lens Oil |            |                  |            |
|---|---|--|-----------------|------------------|------------|------------------|------------|------------------------|------------|------------------|------------|------------------------|------------|------------------|------------|
|   |   | Standard   |                 | High Contrast    |            | High Resolution  |            | Standard               |            | High Resolution  |            | Standard               |            | High Resolution  |            |
|   |   | Condenser Module   | DIC Slider      | Condenser Module | DIC Slider | Condenser Module | DIC Slider | Condenser Module       | DIC Slider | Condenser Module | DIC Slider | Condenser Module       | DIC Slider | Condenser Module | DIC Slider |
| 10x   | Plan Fluor 10x<br>Plan Apo 10x<br>S Fluor 10x   | LWD N1 Dry   | 10x             | —                |            | —                |            | —                      |            | —                |            | —                      |            | —                |            |
|   | Plan Fluor 20x<br>Plan Apo 20x<br>S Fluor 20x<br>Plan Fluor 20x MI<br>Plan Apo VC 20x | LWD N2 Dry   | 20x             | LWD N1 Dry       | 20x-C      |                  |            | HNA N2 Dry             | 20x        |                  |            | HNA N2 Oil             | 20x        |                  |            |
| 20x   | Plan Fluor ELWD 20xC<br>S Plan Fluor ELWD 20xC  | LWD N1 Dry   | 20x I<br>20x II | —                |            |                  |            | —                      |            |                  |            | —                      |            |                  |            |
|   | Plan Fluor 40x<br>Plan Apo 40x<br>S Fluor 40x   | LWD N2 Dry   | 40x I           | LWD N1 Dry       | 40x I-C    | HNA N2 Dry       | 40x I      | HNA N2 Oil             | 40xl       | HNA N2 Oil       | 40x II     | HNA N2 Oil             | 40x III    | HNA N2 Oil       | 40x III    |
| 40x   | Plan Fluor 40x Oil<br>S Fluor 40x Oil   |  | 40x II          | —                |            |                  | 40x II     |                        | 40x II     |                  |            |                        |            |                  |            |
|   | Plan Apo 40x Oil  |  | 40x III         |                  |            |                  | 40x III    |                        | 40x III    |                  |            |                        |            |                  |            |
|   | Plan Fluor ELWD 40xC<br>S Plan Fluor ELWD 40xC  | LWD N1 Dry   | 40x IV          | —                |            | —                |            | —                      |            | —                |            | —                      |            | —                |            |
| 60x   | Plan Apo 60x<br>Plan Apo VC 60x Oil<br>Apo TIRF 60x Oil                               | LWD N2 Dry   | 60x I           | —                |            | LWD NR Dry       | 60x I      | HNA N2 Dry             | 60x I      | HNA NR Dry       | 60x I      | HNA N2 Oil             | 60x I      | HNA NR Oil       | 60x I      |
|   | Plan Fluor 60x Oil<br>Plan Fluor 60x  |  | 60x II          |                  |            |                  | 60x II-R   |                        | 60x II     |                  | 60x II-R   |                        | 60x II     |                  | 60x II-R   |
|   | Plan Apo VC 60xA WI   |  | 60x IV          |                  |            |                  | 60x IV-R   |                        | 60x IV     |                  | 60x IV-R   |                        | 60x IV     |                  | 60x IV-R   |
|   | Plan Fluor ELWD 60xC<br>S Plan Fluor ELWD 60xC  | LWD N1 Dry   | 60x III         |                  |            | —                |            | —                      |            | —                |            | —                      |            | —                |            |
|   | Plan Apo VC 100x Oil<br>Apo TIRF 100x Oil<br>Plan Fluor 100x                          | LWD N2 Dry   | 100x I          |                  |            | LWD NR Dry       | 100x I-R   | HNA N2 Dry             | 100x I     | HNA NR Dry       | 100x I-R   | HNA N2 Oil             | 100x I     | HNA NR Oil       | 100x I-R   |
| Plan Fluor 100x Oil<br>Plan Fluor 100x Oil Iris | 100x II   |  | 100x II-R       |                  |            |                  | 100x II    |                        | 100x II-R  |                  | 100x II    |                        | 100x II-R  |                  |            |

For 90i/80i upright microscopes

|                                       |   | Universal Condenser Dry/Motorized Universal Condenser Dry |               |                  |            |                  |            | DIC Condenser Oil |            |                  |            |
|---------------------------------------|---|---|---------------|------------------|------------|------------------|------------|-------------------|------------|------------------|------------|
|                                       |   | Standard  |               | High Contrast    |            | High Resolution  |            | Standard          |            | High Resolution  |            |
|                                       |   | Condenser Module  | DIC Slider    | Condenser Module | DIC Slider | Condenser Module | DIC Slider | Condenser Module  | DIC Slider | Condenser Module | DIC Slider |
| 10x                                   | Plan Apo 10x (Eco)<br>Plan Fluor 10x<br>S Fluor 10x                                   | N1 Dry  | 10x           | —                |            | —                |            | —                 |            | —                |            |
| 20x                                   | Plan Fluor 20x<br>Plan Fluor 20x MI<br>Plan Apo 20x<br>S Fluor 20x<br>Plan Apo VC 20x | N2 Dry  | 20x           | N1 Dry           | 20x-C      |                  |            | N2 Oil            | 20x        |                  |            |
|                                       | Plan Fluor ELWD 20xC<br>S Plan Fluor ELWD 20xC  | N1 Dry  | 20xl<br>20xII | —                |            |                  |            | —                 |            |                  |            |
|                                       | Plan Fluor 40x<br>Plan Apo 40x<br>S Fluor 40x   | N2 Dry  | 40x I         | N1 Dry           | 40xI-C     |                  |            | N2 Oil            | 40x I      |                  |            |
| Plan Fluor 40x Oil<br>S Fluor 40x Oil | 40x II  |   | —             | 40x II           |            |                  |            |                   |            |                  |            |
| Plan Apo 40x Oil                      | 40x III   |   |               | 40x III          |            |                  |            |                   |            |                  |            |
| 40x                                   | Plan Fluor ELWD 40xC<br>S Plan Fluor ELWD 40xC  | N1 Dry  |               | 40x IV           | —          |                  | —          |                   |            |                  |            |
|                                       | Plan Apo 60x<br>Plan Apo VC 60x Oil<br>Apo TIRF 60x Oil                               | N2 Dry  | 60x I         | —                |            | NR Dry           | 60x I-R    | N2 Oil            | 60x I      | NR Oil           | 60x I-R    |
|                                       | Plan Fluor 60x Oil<br>Plan Fluor 60x  |   | 60x II        |                  |            |                  | 60x II-R   |                   | 60x II     |                  | 60x II-R   |
| 60x                                   | Plan Fluor ELWD 60xC<br>S Plan Fluor ELWD 60xC  | N1 Dry  | 60x III       | —                |            | —                |            | —                 |            | —                |            |
|                                       | Plan Apo VC 100x Oil<br>Plan Apo 100x NCG Oil<br>Apo TIRF 100x Oil<br>Plan Fluor 100x | N2 Dry  | 100x I        | NR Dry           | 100x I-R   | N2 Oil           | 100x I     | NR Oil            | 100x I-R   |                  |            |
|                                       | Plan Fluor 100x Oil<br>Plan Fluor 100x Oil Iris                                       |   | 100x II       |                  | 100x II-R  |                  | 100x II    |                   | 100x II-R  |                  |            |

For FN1 microscope for patch clamp experiments

|      |                            | FN-C LWD Condenser |            |
|------|----------------------------|--------------------|------------|
|      |                            | Condenser Module   | DIC Slider |
| 10x  | Plan Fluor 10xW            | N1 Dry             | 10x        |
| 16x  | LWD 16xW (CFI75)           | N2 Dry             | 16xl       |
| 20x  | Fluor 20xW                 |                    | 20x        |
| 40x  | Apo 40xW NIR<br>Fluor 40xW |                    | 40xIII     |
| 60x  | Apo 60xW NIR<br>Fluor 60xW |                    | 60xl       |
| 100x | Plan 100xW                 |                    | 100x-III   |

Epi-fluorescence Filters

Filter Characteristics

|        | Filters            | Wavelengths                        | Characteristics   | i series, Ti series | E series, TS100 |
|--------|--------------------|------------------------------------|---|---------------------|-----------------|
| U<br>V | UV-1A              | EX 365/10<br>DM 400<br>BA 400      | •Narrow band pass—only 365nm (i line) of Mercury spectrum used<br>•Narrow band pass minimizes auto-fluorescence and photo-bleaching                       | ✓                   | ✓               |
|        | UV-2A              | EX 330-380<br>DM 400<br>BA 420     | •Standard filter block for UV   | ✓                   | ✓               |
|        | UV-2B              | EX 330-380<br>DM 400<br>BA 435     | •Darker background than UV-2A   | ✓                   | ✓               |
| V      | UV-2E/C (DAPI)     | EX 340-380<br>DM 400<br>BA 435-485 | •For DAPI, cutting off FITC (green) and TRITC (red)<br>•Soft-coated type for high signal/noise<br>•Band-Pass Barrier Filter used to cut off green and red | ✓                   | ✓               |
|        | V-2A               | EX 380-420<br>DM 430<br>BA 450     | •Standard filter block for V  | ✓                   | ✓               |
| B<br>V | BV-1A              | EX 435/10<br>EM 455<br>BA 470      | •Narrow band pass—only 435nm (g line) of Mercury spectrum used<br>•Narrow band pass minimizes auto-fluorescence and photo-bleaching                       | ✓                   |                 |
|        | BV-2A              | EX 400-440<br>DM 455<br>BA 470     | •Standard filter block for BV   | ✓                   | ✓               |
| B      | B-1A               | EX 470-490<br>DM 505<br>BA 520     | •Narrower excitation range than B-2A<br>•FITC+Counter-stain (TRITC, PI)   | ✓                   |                 |
|        | B-1E               | EX 470-490<br>DM 505<br>BA 520-560 | •For FITC (green), cutting off Rhodamine red<br>•Band-Pass Barrier Filter used to cut off red   | ✓                   |                 |
|        | B-2A               | EX 450-490<br>DM 505<br>BA 520     | •Standard filter block for B<br>•For FITC + Counter-stain (TRITC, PI)   | ✓                   | ✓               |
|        | B-2E               | EX 450-490<br>DM 505<br>BA 520-560 | •Similar to FITC<br>•For FITC (green), cutting off Rhodamine red<br>•Band-Pass Barrier Filter used to cut off red   |                     | ✓               |
|        | B-2E/C (FITC)      | EX 465-495<br>DM 505<br>BA 515-555 | •Soft coated type for high signal/noise<br>•For FITC (green), cutting off Rhodamine red<br>•Band-pass Barrier Filter used to cut off red                  | ✓                   | ✓               |
|        | B-3A               | EX 420-490<br>DM 505<br>BA 520     | •Wide band pass—recommended for halogen illumination only   | ✓                   | ✓               |
|        | G-1B               | EX 546/10<br>DM 575<br>BA 590      | •Narrow band pass—only 546nm (e line) of Mercury spectrum used<br>•Narrow band pass minimizes auto-fluorescence and photo-bleaching                       | ✓                   | ✓               |
| G      | G-2A               | EX 510-560<br>DM 575<br>BA 590     | •Standard filter block for G  | ✓                   | ✓               |
|        | G-2B               | EX 510-560<br>DM 575<br>BA 610     | •610nm barrier provides darker background and deep red emission   | ✓                   |                 |
|        | G-2E/C (TRITC)     | EX 540/25<br>DM 565<br>BA 605/55   | •For TRITC (Rhodamine)<br>•Soft coated type for high signal/noise<br>•Band-Pass Barrier Filter used to cut off reds above 643nm                           | ✓                   | ✓               |
| Y      | Y-2E/C (Texas Red) | EX 540-580<br>DM 595<br>BA 600-660 | •For Texas Red®<br>•Soft coated type for high signal/noise<br>•Band-Pass Barrier Filter used to cut off reds above 660nm                                  | ✓                   | ✓               |

Filters for Fluorescent Protein

| Filters | Wavelengths                 | i series, Ti series | E series, TS100 |
|---------|-----------------------------|---------------------|-----------------|
| BFP     | EX380/30, DM420, BA460/50   | ✓                   |                 |
| CFP     | EX436/20, DM455, BA480/40   | ✓                   |                 |
| CFP HQ* | EX420-445, DM450, BA460-510 | ✓                   |                 |
| GFP-L   | EX480/40, DM505, BA510      | ✓                   | ✓               |
| GFP-B   | EX480/40, DM505, BA535/50   | ✓                   | ✓               |
| GFP HQ* | EX455-485, DM495, BA500-545 | ✓                   |                 |
| YFP     | EX500/20, DM515, BA535/30   | ✓                   |                 |
| YFP HQ* | EX490-500, DM510, BA520-560 | ✓                   |                 |

\*Each filter/mirror has a very sharp rising edge at the corresponding wavelength, minimizing signal crossover.

Other Filters

| Filters | Wavelengths               | i series, Ti series | E series, TS100 |
|---------|---------------------------|---------------------|-----------------|
| Cy3     | EX535/50, DM565, BA610/75 | ✓                   |                 |
| Cy5     | EX620/60, DM660, BA700/75 | ✓                   |                 |
| Cy7     | EX710/75, DM750, BA810/90 | ✓                   |                 |

Multi-Band Filters



















| Filters | Abbreviations | Applications          | i series, Ti series | E series, TS100 |
|---------|---------------|-----------------------|---------------------|-----------------|
| Dual    | F-R           | FITC, Rhodamine       | ✓                   | ✓               |
|         | F-T           | FITC, Texas Red       | ✓                   | ✓               |
| Triple  | D-F           | DAPI, FITC            | ✓                   |                 |
|         | D-F-R         | DAPI, FITC, Rhodamine | ✓                   | ✓               |
|         | D-F-T         | DAPI, FITC, Texas Red | ✓                   | ✓               |

Filters for SMZ1500/1000/800

| Filters | Wavelengths                 |
|---------|-----------------------------|
| GFP-L   | EX460-500, DM505, BA510     |
| GFP-B   | EX460-500, DM505, BA510-560 |

Note:  
The lineup is constantly updated. For the latest information, please contact your local Nikon representative. The excitation filters or barrier filters in each filter cube are interchangeable. For custom setup, blank cubes without filters are also available. Please consult with your local Nikon distributor for a complete list of filters locally available or inquire about special custom filter combinations.

Dimensional Diagrams



Eyepoint height: when PD is 64mm      Unit: mm

Unit: mm